OC 6000E

Product Data Sheet

BVP10 369B1878G5001

Valve position module base

MARKED SUPPLY VOLTAGE	NETWORK CONNECTION HARDWARE	MODULE MATING INTERFACE	VALVE-CIRCUIT TERMINATION CAPACITY
24 V DC	**2 shielded RJ45 sockets**	**3 multipole board receptacles**	**48 removable terminal positions**

General Electric BVP10 369B1878G5001 is the connection base associated with compatible OC 6000e MVP-series valve-position electronics. It provides the module and field-terminal interface for configured valve-control circuits in turbine and industrial process-control equipment.

01 VERIFIED TECHNICAL DATA

Marked supply voltage	24 V DC
Network connection hardware	2 shielded RJ45 sockets
Module mating interface	3 multipole board receptacles
Valve-circuit termination capacity	48 removable terminal positions
Chassis fixing points	4 panel mounting holes
Module retention	2 rotary locking cams
Grounding connection	1 protective-earth clamping point
Rail retention	Spring-latch DIN rail fixing

Values follow the unit photographs and applicable documentation identified on page 2.

02 ADDITIONAL PRODUCT DATA

Naked product size	17.30 x 12.50 x 6.30 cm
Naked product weight	0.40kg

03 DOCUMENTED USE SETTINGS

Electricity Production and Combined Heat Generation: Electricity and Heat Production.

Petroleum Production and Natural Gas Processing: Oil Production and Processing.

Chemical Production and Petrochemical Processing: Chemical Production and Processing.

04 SYSTEM COMPATIBILITY

General Electric BVP10 369B1878G5001 is the connection base associated with compatible OC 6000e MVP-series valve-position electronics. It provides the module and field-terminal interface for configured valve-control circuits in turbine and industrial process-control equipment.

05 PRODUCT EVIDENCE

Exact-unit nameplate and connector photographs; GE OC 6000e platform overview, I/O interfaces

AMIKON PRODUCT SUPPORT

+86-18020776786 INFO@AMIKON.CN **AMIKONG.COM**