

SCALANCE XF208

Product Data Sheet

6GK5208-0BA00-2AF2

Managed Industrial Ethernet switch

ETHERNET PORTS	COPPER LINK RATES	DC SUPPLY	MAXIMUM SUPPLY CURRENT
8 RJ45	10/100 Mbit/s	24 V, 18 to 32 V	0.13 A

Siemens 6GK5208-0BA00-2AF2 is the SCALANCE XF208 managed Industrial Ethernet switch. It supplies eight copper connections for configured industrial communication in manufacturing and process automation networks.

01

VERIFIED TECHNICAL DATA

Ethernet ports	8 RJ45
Copper link rates	10/100 Mbit/s
DC supply	24 V, 18 to 32 V
Maximum supply current	0.13 A
Power loss	3.12 W
Signaling contact	24 V DC, 0.1 A
Power connector	4-pole terminal
Signaling connector	2-pole terminal
Configuration memory	C-PLUG, optional
Normal operating ambient	-40 to +60 deg C

ADDITIONAL PRODUCT DATA

Horizontal maximum ambient	+40 deg C
Storage ambient	-40 to +70 deg C
Relative humidity	95% maximum, non-condensing
Ingress protection	IP20
PROFINET conformance	Class B

DOCUMENTED USE SETTINGS

Industrial Production and Manufacturing Process Automation: Discrete Industrial Manufacturing.

Chemical Manufacturing and Industrial Process Production: Industrial Chemical Process Production.

Drinking Water Production and Wastewater Treatment: Drinking Water Process Treatment.

SYSTEM COMPATIBILITY

Siemens 6GK5208-0BA00-2AF2 is the SCALANCE XF208 managed Industrial Ethernet switch. It supplies eight copper connections for configured industrial communication in manufacturing and process automation networks.

PRODUCT EVIDENCE

Siemens SCALANCE XF208 technical documentation

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM