ABB FLASHDROP MFDT-01

Product Data Sheet

MFDT-01

Handheld Drive Configuration Tool

TYPICAL USE PER CHARGE	TYPICAL CHARGING TIME	OPERATING TEMPERATURE	BASE ENCLOSURE MATERIAL
4 hours	**1.5 hours**	**-10 to 40 deg C, no frost**	**PC/ABS and PA66+25%GF**

ABB MFDT-01 is a handheld drive configuration tool in the ABB FlashDrop MFDT-01 family. It serves compatible installed control equipment in the documented system configuration.

01 VERIFIED TECHNICAL DATA

Typical use per charge	4 hours
Typical charging time	1.5 hours
Operating temperature	-10 to 40 deg C, no frost
Base enclosure material	PC/ABS and PA66+25%GF
Panel construction	PC/ABS with clear PC
EMC standard	IEC/EN 61800-3:2004

Values follow the unit photographs and applicable documents identified on page 2.

02 ADDITIONAL PRODUCT DATA

Naked product size	15.8 x 8.8 x 5.5cm
Naked product weight	0.45kg

03 DOCUMENTED USE SETTINGS

Packaging Production and Material Converting: Carton Packaging Process Control.

Food Processing and Beverage Production: Food Processing and Production.

Manufacturing and Industrial Production Automation: Industrial Manufacturing Process Automation.

04 SYSTEM COMPATIBILITY

Match MFDT-01 to the documented ABB FlashDrop MFDT-01 arrangement. Confirm the supplied execution, connections and required companion equipment before integration.

05 PRODUCT EVIDENCE

ABB FlashDrop User manual, technical data pp.51 to 52

AMIKON PRODUCT SUPPORT

+86-18020776786 INFO@AMIKON.CN **AMIKONG.COM**