

MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

Reference package for procurement and maintenance review

SIEMENS

6SL3210-5FE15-0UF0

THREE PHASE SERVO DRIVE

Used with the applicable SINAMICS V90 PROFINET configuration.

REFERENCE PACKAGE

OFFICIAL DOCUMENT

Selected official manufacturer pages follow this cover.

Source: Siemens 6SL3210-5FE15-0UF0 official product technical data, applicable pages 1



Figure similar

MLFB-Ordering data

6SL3210-5FE15-0UF0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		Ambient conditions	
Input		Cooling	Fan
Number of phases	3 AC	Installation altitude	1000 m
Line voltage	380 ... 480 V +10 % -15 %	Ambient temperature	
Line frequency	45 ... 66 Hz	Operation	0 ... 45 °C
Output		Storage	-40 ... 70 °C
Rated power	5.00 kW	Relative humidity	
Rated current (IN)	12.60 A	Max. operation	90 %
Max. output current	37.80 A	Standards	
Inputs / outputs		Compliance with standards	CE, KC, cULus, EAC, C-Tick (RCM)
Standard digital inputs		Communication	
Number	4	Communication	PROFINET
Digital outputs			
Number	2		
Mechanical data			
Degree of protection	IP20 / UL open type		
Frame size	FSC		
Net weight	5.65 kg		
Width	140.0 mm		
Height	260.0 mm		
Depth	240.0 mm		