SIMATIC ET 200S TM-P15S23-A0

Product Data Sheet

6ES7193-4CD20-0AA0

Power Module Terminal Base

CONNECTION POSITION COUNT	TERMINAL CONSTRUCTION	AUX1 EXTERNAL ACCESS	AUX1 BUS CONTINUITY
2 x 3	**Screw contacts**	**A4 / A8**	**Interrupted at potential-group boundary**

Siemens 6ES7193-4CD20-0AA0 is a power module terminal base in the SIMATIC ET 200S TM-P15S23-A0 range. It supports permanent field wiring for compatible distributed I/O stations.

01 VERIFIED TECHNICAL DATA

Connection position count	2 x 3
Terminal construction	Screw contacts
AUX1 external access	A4 / A8
AUX1 bus continuity	Interrupted at potential-group boundary
Bare wire section	0.14 to 2.5 mm², solid or flexible
Ferruled flexible wire	0.14 to 1.5 mm²
Wire stripping length	11 mm
Insulation diameter	3.1 mm at 1.5 mm²; 3.8 mm at 2.5 mm²
Two-wire ferrule capacity	1.5 mm² total
Uninsulated ferrule length	12 mm maximum, DIN 46228 form A

Values follow the applicable manufacturer documents identified on page 2.

02 ADDITIONAL PRODUCT DATA

Wire release tool	3 mm screwdriver
Screw tightening torque	0.4 to 0.7 N m

03 DOCUMENTED USE SETTINGS

Food Processing and Beverage Production Industries: Food Processing and Packaging.

Water Supply and Wastewater Treatment Processes: Drinking Water Treatment.

Industrial Manufacturing and Automated Product Assembly: Industrial Component Manufacturing.

04 SYSTEM COMPATIBILITY

Match 6ES7193-4CD20-0AA0 to the accepted SIMATIC ET 200S TM-P15S23-A0 configuration and associated parts before integration.

05 PRODUCT EVIDENCE

Siemens SIMATIC ET 200S TM-P15S23-A0 applicable manufacturer data

AMIKON PRODUCT SUPPORT

+86-18020776786 INFO@AMIKON.CN **AMIKONG.COM**