

SIMATIC ET 200S TM-P15S23-A1

Product Data Sheet

6ES7193-4CC20-0AA0

Power Module Terminal Base

CONNECTION POSITION COUNT	TERMINAL CONSTRUCTION	AUX1 EXTERNAL ACCESS	AUX1 BUS CONTINUITY
2 x 3	Screw contacts	A4 / A8	Continuous to adjacent group

Siemens 6ES7193-4CC20-0AA0 is a power module terminal base in the SIMATIC ET 200S TM-P15S23-A1 range. It supports permanent field wiring for compatible distributed I/O stations.

01

VERIFIED TECHNICAL DATA

Connection position count	2 x 3
Terminal construction	Screw contacts
AUX1 external access	A4 / A8
AUX1 bus continuity	Continuous to adjacent group
Bare wire section	0.14 to 2.5 mm ² , solid or flexible
Ferruled flexible wire	0.14 to 1.5 mm ²
Wire stripping length	11 mm
Insulation diameter	3.1 mm at 1.5 mm ² ; 3.8 mm at 2.5 mm ²
Two-wire ferrule capacity	1.5 mm ² total
Uninsulated ferrule length	12 mm maximum, DIN 46228 form A

ADDITIONAL PRODUCT DATA

Wire release tool	3 mm screwdriver
Screw tightening torque	0.4 to 0.7 N m

DOCUMENTED USE SETTINGS

Packaging Manufacturing and Industrial Filling Production: Industrial Packaging Production.

Textile Manufacturing and Industrial Fabric Processing: Yarn and Fiber Production.

Water Supply and Wastewater Treatment Processes: Drinking Water Treatment.

SYSTEM COMPATIBILITY

Match 6ES7193-4CC20-0AA0 to the accepted SIMATIC ET 200S TM-P15S23-A1 configuration and associated parts before integration.

PRODUCT EVIDENCE

Siemens SIMATIC ET 200S TM-P15S23-A1 applicable manufacturer data