

SIMATIC DP PROFIBUS RS485

Product Data Sheet

6ES7972-0BA12-0XA0

Vertical PROFIBUS Screw Connector

PROFIBUS DATA RATE	BUS CABLE CONNECTION COUNT	EQUIPMENT CONNECTION COUNT	CABLE TERMINATION
9.6 kbit/s to 12 Mbit/s	2	1	Screw terminals

Siemens 6ES7972-0BA12-0XA0 is a vertical profibus screw connector in the SIMATIC DP PROFIBUS RS485 range. It supports the documented automation configuration in industrial equipment.

01

VERIFIED TECHNICAL DATA

PROFIBUS data rate	9.6 kbit/s to 12 Mbit/s
Bus cable connection count	2
Equipment connection count	1
Cable termination	Screw terminals
Station connector	9-pin D-sub male
Terminating network	Integrated resistor combination, slide-switch selectable
Cable outlet angle	90°
Enclosure material	Plastic
Locking construction	Screwed joint
Operating temperature	-25 to 60 deg C

ADDITIONAL PRODUCT DATA

Storage and transport temperature	-40 to 70 deg C
Ingress protection	IP20
Programming-device socket	Not provided
Cable strain relief	Provided
Silicone content	Silicone-free

DOCUMENTED USE SETTINGS

Industrial Manufacturing and Automated Product Assembly: Industrial Component Manufacturing.

Automotive Manufacturing and Vehicle Component Production: Vehicle Component Manufacturing.

Food Processing and Beverage Production Industries: Food Processing and Packaging.

SYSTEM COMPATIBILITY

Match 6ES7972-0BA12-0XA0 to the accepted SIMATIC DP PROFIBUS RS485 configuration and associated parts before integration.

PRODUCT EVIDENCE

Siemens SIMATIC DP PROFIBUS RS485 applicable manufacturer data