

SIRIUS S00 RELAY MOUNTING

Product Data Sheet

3RU2916-3AA01

Overload Relay Terminal Support

RELAY FRAME SIZE	COMPATIBLE RELAY FAMILIES	MAIN-CIRCUIT CONTACT METHOD	OPERATING AMBIENT
S00	3RU21 / 3RB30 / 3RB31 / 3RR2	Screw terminals	-20 to 70 deg C

Siemens 3RU2916-3AA01 is a overload relay terminal support in the SIRIUS S00 Relay Mounting range. It supports the documented automation configuration in industrial equipment.

01

VERIFIED TECHNICAL DATA

Relay frame size	S00
Compatible relay families	3RU21 / 3RB30 / 3RB31 / 3RR2
Main-circuit contact method	Screw terminals
Operating ambient	-20 to 70 deg C
Storage ambient	-50 to 80 deg C
Front ingress protection	IP20
Front touch protection	Finger-safe with vertical front contact
Fastening system	Screw fixing or snap-on to 35 mm DIN rail
Bare conductor section	0.5 to 4 mm², solid or stranded
Ferruled fine-stranded section	0.5 to 2.5 mm²

ADDITIONAL PRODUCT DATA

Conductor AWG interval	20 to 12
------------------------	----------

DOCUMENTED USE SETTINGS

Pulp Production and Paper Manufacturing Processes: Pulp Processing and Preparation.

Packaging Manufacturing and Industrial Filling Production: Industrial Packaging Production.

Chemical Manufacturing and Industrial Material Processing: Industrial Chemical Manufacturing.

SYSTEM COMPATIBILITY

Match 3RU2916-3AA01 to the accepted SIRIUS S00 Relay Mounting configuration and associated parts before integration.

PRODUCT EVIDENCE

Siemens SIRIUS S00 Relay Mounting applicable manufacturer data

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM