ET 200S

Product Data Sheet

6ES7132-4BF00-0AA0

digital output module

DIGITAL OUTPUTS	RATED LOAD VOLTAGE	RATED OUTPUT CURRENT	BACKPLANE CURRENT
8	**24 V DC**	**0.5 A per channel**	**10 mA max.**

Siemens 6ES7132-4BF00-0AA0 is a digital output module for the ET 200S product family. It provides 8 for distributed automation, machine control, and industrial communication tasks.

01 VERIFIED TECHNICAL DATA

Digital outputs	8
Rated load voltage	24 V DC
Rated output current	0.5 A per channel
Backplane current	10 mA max.
Power loss	1.5 W typ.
Lamp load	5 W max.
Load resistance	48 to 3,400 ohm
Output delay 0 to 1	300 microseconds max.
Output delay 1 to 0	600 microseconds max.
Resistive switching frequency	100 Hz max.

Values follow the applicable manufacturer documents identified on page 2.

02 ADDITIONAL PRODUCT DATA

Inductive switching frequency	2 Hz max.
Group current	4 A max. at 60 deg C
Shielded cable length	1,000 m max.
Isolation test	500 V DC

03 DOCUMENTED USE SETTINGS

Automotive Production and Assembly: Body production lines.

Water Treatment and Distribution: Pumping station automation.

Food Processing and Packaging: Packaging machine control.

04 SYSTEM COMPATIBILITY

Install 6ES7132-4BF00-0AA0 only in the documented ET 200S environment and verify the applicable terminal, bus, or module interface before wiring.

05 PRODUCT EVIDENCE

Siemens product data sheet

AMIKON PRODUCT SUPPORT

+86-18020776786 INFO@AMIKON.CN **AMIKONG.COM**