ET 200SP

Product Data Sheet

6ES7193-6BP00-0BA0

Standard ET 200SP BaseUnit

BASEUNIT TYPE	TERMINAL TYPE	RATED VOLTAGE	P1 / P2 CURRENT
A0	**Push-in**	**24 V DC**	**10 A maximum**

Siemens 6ES7193-6BP00-0BA0 is a standard et 200sp baseunit for the ET 200SP product family. It provides the documented baseunit type of A0 for compatible industrial automation and electrical systems.

01 VERIFIED TECHNICAL DATA

BaseUnit type	A0
Terminal type	Push-in
Rated voltage	24 V DC
P1 / P2 current	10 A maximum
Process-terminal current	2 A maximum
Process terminals	16
AUX terminals	0
Potential group	Continued from left
Conductor range	0.14 to 2.5 mm²
Operating temperature	-30 to +60 °C

Values follow the applicable manufacturer documents identified on page 2.

02 ADDITIONAL PRODUCT DATA

Naked product size	1.50 x 11.70 x 3.50 cm
Naked product weight	0.04 kg

03 DOCUMENTED USE SETTINGS

Vehicle Assembly and Robotic Production Lines: Robotic assembly cells connecting distributed sensors and field actuators.

Pumping Stations and Treatment Process Control: Pumping stations handling motor feedback and valve status signals.

Conveyor Sorting and Warehouse Automation Systems: Conveyor sections exchanging discrete status and command signals.

04 SYSTEM COMPATIBILITY

Install 6ES7193-6BP00-0BA0 only in the documented ET 200SP environment after confirming the exact order code, module position and connection method. Match every supply, signal and network interface to the applicable Siemens data before energization.

05 PRODUCT EVIDENCE

Siemens product data sheet

AMIKON PRODUCT SUPPORT

+86-18020776786 INFO@AMIKON.CN **AMIKONG.COM**