

ET 200S

Product Data Sheet

6ES7132-4BB01-0AB0

Two-channel digital output module

DIGITAL OUTPUTS	RATED LOAD VOLTAGE	RATED OUTPUT CURRENT	SHORT-CIRCUIT THRESHOLD
2	24 V DC	0.5 A per channel	1.5 A typical

Siemens 6ES7132-4BB01-0AB0 is a two-channel digital output module for the ET 200S product family. It provides the documented digital outputs of 2 for compatible industrial automation and electrical systems.

01

VERIFIED TECHNICAL DATA

Digital outputs	2
Rated load voltage	24 V DC
Rated output current	0.5 A per channel
Short-circuit threshold	1.5 A typical
Lamp load	2.5 W maximum
Module current	1 A maximum
Diagnostics	Wire break and short circuit
Substitute values	Configurable 0 / 1
Resistive switching frequency	100 Hz maximum
Isolation test	500 V DC

ADDITIONAL PRODUCT DATA

Isochronous operation	Supported
-----------------------	-----------

DOCUMENTED USE SETTINGS

Vehicle Assembly and Robotic Production Lines: Robotic assembly cells connecting distributed sensors and field actuators.

Pumping Stations and Treatment Process Control: Pumping stations handling motor feedback and valve status signals.

Conveyor Sorting and Warehouse Automation Systems: Conveyor sections exchanging discrete status and command signals.

SYSTEM COMPATIBILITY

Install 6ES7132-4BB01-0AB0 only in the documented ET 200S environment after confirming the exact order code, module position and connection method. Match every supply, signal and network interface to the applicable Siemens data before energization.

PRODUCT EVIDENCE

Siemens product data sheet

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM