

ET 200SP

Product Data Sheet

6ES7193-6BP20-0BA0

Auxiliary-terminal ET 200SP BaseUnit

BASEUNIT TYPE	TERMINAL TYPE	RATED VOLTAGE	P1 / P2 CURRENT
A0	Push-in	24 V DC	10 A maximum

Siemens 6ES7193-6BP20-0BA0 is a auxiliary-terminal et 200sp baseunit for the ET 200SP product family. It provides the documented baseunit type of A0 for compatible industrial automation and electrical systems.

01

VERIFIED TECHNICAL DATA

BaseUnit type	A0
Terminal type	Push-in
Rated voltage	24 V DC
P1 / P2 current	10 A maximum
AUX current	10 A maximum
Process-terminal current	2 A maximum
Process terminals	16
AUX terminals	10
Potential group	Continued from left
Conductor range	0.14 to 2.5 mm ²

ADDITIONAL PRODUCT DATA

Isolation test

707 V DC

DOCUMENTED USE SETTINGS

Vehicle Assembly and Robotic Production Lines: Robotic assembly cells connecting distributed sensors and field actuators.

Pumping Stations and Treatment Process Control: Pumping stations handling motor feedback and valve status signals.

Conveyor Sorting and Warehouse Automation Systems: Conveyor sections exchanging discrete status and command signals.

SYSTEM COMPATIBILITY

Install 6ES7193-6BP20-0BA0 only in the documented ET 200SP environment after confirming the exact order code, module position and connection method. Match every supply, signal and network interface to the applicable Siemens data before energization.

PRODUCT EVIDENCE

Siemens product data sheet

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM