ALLEN-BRADLEY CONTROLLOGIX

Product Data Sheet

1756-L61

ControlLogix programmable controller

USER MEMORY	I/O MEMORY	BACKPLANE CURRENT AT 5.1 V	BACKPLANE CURRENT AT 24 V
2 MB	**478 KB**	**1200 mA**	**14 mA**

Allen-Bradley 1756-L61 is a controllogix programmable controller for the Allen-Bradley ControlLogix product family. It provides the documented interfaces and electrical characteristics for compatible industrial automation configurations.

01 VERIFIED TECHNICAL DATA

User memory	2 MB
I/O memory	478 KB
Backplane current at 5.1 V	1200 mA
Backplane current at 24 V	14 mA
Power dissipation	3.5 W
Thermal dissipation	11.9 BTU/h
Serial communication	RS-232
Programming cable	1756-CP3 or 1747-CP3
Battery	1756-BA2 lithium
Operating temperature	0 to 60 °C

Values follow the applicable manufacturer documents identified on page 2.

02 ADDITIONAL PRODUCT DATA

Naked product size	22 x 17.3 x 5.2 cm
Naked product weight	0.55 kg

03 DOCUMENTED USE SETTINGS

Automotive Manufacturing: Vehicle Assembly Production.

Food and Beverage: Beverage Production Operations.

Chemical Processing: Specialty Chemical Production.

04 SYSTEM COMPATIBILITY

Use 1756-L61 only in the documented Allen-Bradley ControlLogix environment and confirm the applicable chassis, terminal assembly and electrical supply before connection.

05 PRODUCT EVIDENCE

Rockwell Automation manufacturer documentation

AMIKON PRODUCT SUPPORT

+86-18020776786 INFO@AMIKON.CN **AMIKONG.COM**