SIMATIC S7-200 SMART

Product Data Sheet

6ES7288-2DR08-0AA0

SIMATIC S7-200 SMART SM DR08 relay output module

OUTPUT CHANNELS	COIL SUPPLY	DC SWITCHING RANGE	AC SWITCHING RANGE
8 relay outputs	**24 V DC**	**5 to 30 V DC**	**5 to 250 V AC**

Siemens 6ES7288-2DR08-0AA0 is a SIMATIC S7-200 SMART SM DR08 relay output module designed for SIMATIC S7-200 SMART automation equipment. It provides the documented interfaces, electrical characteristics and installation format associated with this exact order number.

01 VERIFIED TECHNICAL DATA

Output channels	8 relay outputs
Coil supply	24 V DC
DC switching range	5 to 30 V DC
AC switching range	5 to 250 V AC
Maximum output current	2 A per output
Common current limit	8 A
Width	45 mm
Height	100 mm
Depth	81 mm
Net weight	166.3 g

Values follow the applicable manufacturer documents identified on page 2.

02 ADDITIONAL PRODUCT DATA

Naked product size	4.5 x 10 x 8.1 cm
Naked product weight	0.166 kg

03 DOCUMENTED USE SETTINGS

Production Automation Systems: Machine sequencing and interlocking.

Utility Process Control: Pump-station equipment control.

Facility Automation Networks: Central plant equipment monitoring.

04 SYSTEM COMPATIBILITY

6ES7288-2DR08-0AA0 is a SIMATIC S7-200 SMART SM DR08 relay output module in the SIMATIC S7-200 SMART family. Confirm the complete order code, installed position and documented output channels of 8 relay outputs before wiring or mechanical installation.

05 PRODUCT EVIDENCE

Siemens manufacturer documentation for 6ES7288-2DR08-0AA0

AMIKON PRODUCT SUPPORT

+86-18020776786 INFO@AMIKON.CN **AMIKONG.COM**