

SIMATIC ET 200S

Product Data Sheet

6ES7132-4BF50-0AB0

8-channel 24 V DC sink digital output module, five-piece pack

DIGITAL OUTPUTS	RATED LOAD VOLTAGE	RATED OUTPUT CURRENT	TOTAL OUTPUT CURRENT
8 M-type sink outputs	24 V DC	0.5 A per channel	4 A

Siemens 6ES7132-4BF50-0AB0 is a 8-channel 24 V DC sink digital output module, five-piece pack in the SIMATIC ET 200S family. It is identified for compatible SIMATIC ET 200S installations and should be selected by its complete order number and documented interface.

01

VERIFIED TECHNICAL DATA

Digital outputs	8 M-type sink outputs
Rated load voltage	24 V DC
Rated output current	0.5 A per channel
Total output current	4 A
Reverse polarity protection	Yes
Backplane current	10 mA maximum at 3.3 V DC
No-load current from L+	5 mA maximum
Typical power loss	1.5 W
Process address space	1 byte
Short-circuit protection	Yes; 1.5 A typical response threshold

ADDITIONAL PRODUCT DATA

Inductive shutdown limit	47 V typical
Lamp load	5 W maximum
Isochronous mode	Supported
Packing quantity	5 modules

DOCUMENTED USE SETTINGS

Marine, Shipbuilding and Port Industries: Shipbuilding and marine sites.

Metals, Mining and Mineral Industries: Steel and nonferrous metal sites.

Water Supply and Wastewater Industries: Municipal water and wastewater sites.

SYSTEM COMPATIBILITY

6ES7132-4BF50-0AB0 belongs to the SIMATIC ET 200S family and provides the documented role of 8-channel 24 V DC sink digital output module, five-piece pack. Review the exact order number before assigning it to the installed architecture.

PRODUCT EVIDENCE

Siemens manufacturer documentation

AMIKON PRODUCT SUPPORT

+86-18020776786

INFO@AMIKON.CN

AMIKONG.COM