SERIES 90-30

Product Data Sheet

IC693CPU350-DH

single-slot CPU 350 controller

PROCESSOR	PROCESSOR SPEED	USER MEMORY	TYPICAL BOOLEAN SCAN
80386EX	**25 MHz**	**32 KB**	**0.22 ms per 1K logic**

GE Fanuc IC693CPU350-DH is a single-slot CPU 350 controller for the Series 90-30 platform. It provides the documented electrical, communication or control role defined for this exact article and revision.

01 VERIFIED TECHNICAL DATA

Processor	80386EX
Processor speed	25 MHz
User memory	32 KB
Typical Boolean scan	0.22 ms per 1K logic
Discrete inputs	2,048 points
Discrete outputs	2,048 points
Register memory	9,999 words
Analog inputs	2,048 words
Analog outputs	512 words
Baseplates	8 maximum

Values follow the applicable manufacturer documents identified on page 2.

02 ADDITIONAL PRODUCT DATA

Backplane load	670 mA at 5 V DC
Serial protocol	SNP and SNP-X slave
Memory storage	RAM and flash
Real-time clock	Battery backed

03 DOCUMENTED USE SETTINGS

Metals and Mineral Resource Production Sectors: Steel and nonferrous metal production across industrial sites.

Chemical and Petrochemical Manufacturing Infrastructure: Bulk chemical manufacturing across integrated industrial complexes.

Urban and Mainline Rail Transport Infrastructure: Urban rail transit across metropolitan passenger networks.

04 SYSTEM COMPATIBILITY

IC693CPU350-DH provides the documented function of a single-slot CPU 350 controller in the Series 90-30 platform. Match the complete article and revision with the host architecture before engineering approval.

05 PRODUCT EVIDENCE

GE Fanuc CPU 350 Product Information GFK-1512M

AMIKON PRODUCT SUPPORT

+86-18020776786 INFO@AMIKON.CN **AMIKONG.COM**