VERSAMAX

Product Data Sheet

IC200ALG328D

12-channel 13-bit current output module revision D

OUTPUT CHANNELS	OUTPUT SIGNAL	RESOLUTION	OVERRANGE OUTPUT
12	**4 to 20 mA current sourcing**	**13 bit**	**Approximately 20.38 mA**

GE Fanuc IC200ALG328D is a 12-channel 13-bit current output module revision D for the VersaMax platform. It provides the documented control, interface or service function defined for this exact article and revision.

01 VERIFIED TECHNICAL DATA

Output channels	12
Output signal	4 to 20 mA current sourcing
Resolution	13 bit
Overrange output	Approximately 20.38 mA
External field supply	Required
Backplane current	50 mA maximum at 5 V DC
Output update	All channels each module scan
Load resistance	Dependent on field supply
User power diagnostics	Loss of user-side power
Output default	Configurable hold-last or default

Values follow the applicable manufacturer documents identified on page 2.

02 ADDITIONAL PRODUCT DATA

Host data	12 analog output words
Operating temperature	0 to 60 deg C

03 DOCUMENTED USE SETTINGS

Transportation Infrastructure: Rail and transit infrastructure.

Industrial Manufacturing Facilities: Discrete manufacturing and assembly facilities.

Water and Wastewater Infrastructure: Municipal water treatment facilities.

04 SYSTEM COMPATIBILITY

Install IC200ALG328D only within the documented VersaMax architecture.

05 PRODUCT EVIDENCE

GE Fanuc IC200ALG328 analog output module data

AMIKON PRODUCT SUPPORT

+86-18020776786