

MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

Reference package for procurement and maintenance review

SIEMENS

6SL3203-0CD21-0AA0

SINAMICS LINE REACTOR FOR FSB POWER MODULES

Used with the applicable SINAMICS G120 configuration.

REFERENCE PACKAGE

OFFICIAL DOCUMENT

Selected official manufacturer pages follow this cover.

Source: Official Siemens technical documentation for 6SL3203-0CD21-0AA0

SIEMENS

Product data sheet

6SL3203-0CD21-0AA0


Fig. similar

SINAMICS LINE REACTOR FOR POWER MODULE
FSB 2.2 AND 3,0 KW,
FOOT PRINT

Output current / rated value	9 A
Effective power loss	
• at 50 Hz	9 W
• at 60 Hz	11 W
Connectable conductor cross-section	
• for line supply conductor	6 mm ²
• for load-side outgoing feeder	1.5 mm ²
Design of electrical connection / for PE conductor	M5 stud bolt
Protection class IP	IP20
Width	153 mm
Height	270 mm
Depth	70 mm
Net weight	3.4 kg
Further information	

[Information and download center for Industry Automation and Drives](#)

[Technical documentation \(Motion Control\)](#)

[Industry Mall \(online ordering system\)](#)

[Service & Support \(FAQs, manuals, operating instructions, certificates, characteristics, ...\)](#)

last change:

Mar 1, 2013