PANELVIEW PLUS 7 PERFORMANCE

Product Data Sheet

2711P-T12W22D9P

12.1-inch Widescreen Color Touch Performance Terminal

OPERATOR INPUT	DISPLAY TYPE	DISPLAY DIAGONAL	VIEWING AREA
Analog resistive touch	**TFT color**	**12.1-inch widescreen**	**261 x 163 mm**

Allen-Bradley 2711P-T12W22D9P is a 12.1-inch widescreen color touch performance terminal in the PanelView Plus 7 Performance range. It provides a 1280 x 800 WXGA operator display for compatible FactoryTalk View Machine Edition projects.

01 VERIFIED TECHNICAL DATA

Operator input	Analog resistive touch
Display type	TFT color
Display diagonal	12.1-inch widescreen
Viewing area	261 x 163 mm
Display resolution	1280 x 800 WXGA
Aspect ratio	16:10
Brightness	300 cd/m² or higher
Backlight life	50,000 h minimum at 40 °C
Touch rating	1 million presses
Input voltage	24 V DC nominal, 18 to 30 V DC

Values follow the unit photographs and applicable documents identified on page 2.

02 ADDITIONAL PRODUCT DATA

Maximum power	50 W Series A; 33 W Series B
Ethernet ports	Two 10/100Base-T ports with DLR support
System memory	512 MB RAM Series A; 4 GB RAM Series B
Application storage	Approximately 80 MB Series A; 2 GB Series B
SD card slot	One external storage slot

03 DOCUMENTED USE SETTINGS

Aerospace Manufacturing and Aviation Support Services: Aerospace Component Manufacturing.

Thermal, Hydroelectric and Renewable Power Generation: Thermal Electricity Generation.

Commercial and Institutional Building Operations: Commercial Property Operations.

04 SYSTEM COMPATIBILITY

Integrate 2711P-T12W22D9P with the documented 24 V DC supply, panel cutout and protective enclosure. Match the terminal series to the accepted FactoryTalk View project and firmware baseline.

05 PRODUCT EVIDENCE

Rockwell Automation PanelView Plus 7 Performance Technical Data

AMIKON PRODUCT SUPPORT

+86-18020776786 INFO@AMIKON.CN **AMIKONG.COM**