SIMATIC ET 200S

Product Data Sheet

6ES7151-3BA22-0AB0

IM151-3 PN HF interface

FUNCTION	FAMILY	ORIGIN	WEIGHT
IM151-3 PN HF interface	**SIMATIC ET 200S**	**Germany**	**0.15 kg**

Siemens 6ES7151-3BA22-0AB0 is a IM151-3 PN HF interface for the SIMATIC ET 200S. The values below are limited to the exact documented article.

01 VERIFIED TECHNICAL DATA

Rated voltage	24 V DC
Current consumption	200 mA maximum
Network interface	PROFINET IO
Ethernet ports	2 RJ45 ports
Transmission rate	100 Mbit/s maximum
Maximum modules	63
Maximum address area	256 bytes input and 256 bytes output
Backplane-bus length	2 m maximum
Module width	60 mm
Power loss	Approximately 2 W

02 ADDITIONAL PRODUCT DATA

03 OFFICIAL APPLICATIONS

- Institutional and Retail Buildings: Institutional and public buildings; Retail and commercial properties
- Batch and Continuous Chemical Production: Batch chemical and pharmaceutical production; Continuous chemical and materials processing
- Upstream and Refining Production: Upstream oil and gas production; Petroleum refining and terminal operations

04 SYSTEM COMPATIBILITY

Match 6ES7151-3BA22-0AB0 to the installed SIMATIC ET 200S, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

05 OFFICIAL SOURCES

Technical documentation applicable to 6ES7151-3BA22-0AB0

Selected technical pages; website addresses removed from this reference package.

AMIKON PRODUCT SUPPORT

+86-18020776786 INFO@AMIKON.CN **AMIKONG.COM**