SIMATIC S7-200 SMART

Product Data Sheet

6ES7288-3AR04-0AA0

S7-200 SMART four-channel RTD input module

FUNCTION	FAMILY	ORIGIN	WEIGHT
S7-200 SMART four-channel RTD input	**SIMATIC S7-200 SMART**	**Germany**	**0.15 kg**

Siemens 6ES7288-3AR04-0AA0 is a S7-200 SMART four-channel RTD input module for the SIMATIC S7-200 SMART. The values below are limited to the exact documented article.

01 VERIFIED TECHNICAL DATA

Analog inputs	4
Measurement type	RTD and resistance
Resolution	16 bit
Sensor wiring	2-, 3- or 4-wire
Supply voltage	24 V DC
Supply current	40 mA
Backplane current	80 mA
Power loss	1.5 W
Diagnostics	Open-wire, range and low-voltage
Platform	SIMATIC S7-200 SMART

02 ADDITIONAL PRODUCT DATA

03 OFFICIAL APPLICATIONS

- Food Processing and Beverage Production: Food processing and packaged product production; Beverage production and bottling
- Warehousing and Distribution: Warehouse distribution and order fulfilment; Material handling and goods transfer
- Vehicle and Component Production: Vehicle assembly and precision parts production; Automotive electronics and component manufacturing

04 SYSTEM COMPATIBILITY

Match 6ES7288-3AR04-0AA0 to the installed SIMATIC S7-200 SMART, complete wiring, mating hardware, revision and approved configuration. A similar article number does not establish direct interchangeability.

05 OFFICIAL SOURCES

Official manufacturer documentation applicable to 6ES7288-3AR04-0AA0

Selected official manufacturer pages; embedded web links removed.

AMIKON PRODUCT SUPPORT

+86-18020776786 INFO@AMIKON.CN **AMIKONG.COM**