MANUFACTURER DOCUMENT PACKAGE

Manufacturer's Manual

Reference package for procurement and maintenance review

SIEMENS

6ES7134-4JB00-0AB0

ET 200S TWO-CHANNEL THERMOCOUPLE INPUT MODULE

Used with the applicable SIMATIC ET 200S configuration.

REFERENCE PACKAGE

OFFICIAL DOCUMENT

Selected official manufacturer pages follow this cover.

Source: Siemens official documentation applicable to 6ES7134-4JB00-0AB0

SIEMENS

Data sheet 6ES7134-4JB00-0AB0



Spare part SIMATIC DP, Electronics module for ET 200S, 2 AI TC; 15 mm width, 15 bit+sign +/-80 mV; Characteristic linearization for thermocouples of the types: B, E, J, K, L, N, R, S, T Cycle time 65 ms/channel with SF LED (group fault)

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V; From power module
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	30 mA
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	0.6 W
Address area	
Address space per module	
• Address space per module, max.	4 byte
Analog inputs	
Number of analog inputs	2
permissible input voltage for voltage input (destruction limit), max.	10 V; Permanent
Cycle time (all channels) max.	Number of active channels per module x basic conversion time

Subject to change without notice
© Copyright Siemens

Technical unit for temperature measurement adjustable	No; Celsius
Input ranges (rated values), voltages	
• -80 mV to +80 mV	Yes
— Input resistance (-80 mV to +80 mV)	1 MΩ
Input ranges (rated values), thermocouples	
• Type B	Yes
— Input resistance (Type B)	1 MΩ
• Type E	Yes
— Input resistance (Type E)	1 MΩ
• Type J	Yes
— Input resistance (type J)	1 MΩ
• Type K	Yes
— Input resistance (Type K)	1 MΩ
• Type L	Yes
— Input resistance (Type L)	1 MΩ
• Type N	Yes
— Input resistance (Type N)	1 MΩ
• Type R	Yes
— Input resistance (Type R)	1 MΩ
• Type S	Yes
— Input resistance (Type S)	1 MΩ
• Type T	Yes
— Input resistance (Type T)	1 MΩ
Thermocouple (TC)	
Temperature compensation	
— internal temperature compensation	Not possible
— external temperature compensation with compensations socket	Yes; possible, one external compensating box per channel
Characteristic linearization	
• parameterizable	Yes; Type B, E, J, K, L, N, R, S, T to IEC 584
Cable length	
• shielded, max.	50 m

Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit; 15 bit + sign
• Integration time, parameterizable	Yes
• Integration time (ms)	16,7 / 20 ms
• Interference voltage suppression for interference frequency f1 in Hz	50 / 60 Hz
• Conversion time (per channel)	65 ms; 55 / 65 ms (additional 20 ms on activated wire-break test)

Subject to change without notice
© Copyright Siemens

Encoder	
Connection of signal encoders	
• for voltage measurement	Yes

Errors/accuracies	
Operational error limit in overall temperature range	
• Voltage, relative to input range, (+/-)	0.6 %
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to input range, (+/-)	0.4 %

Interrupts/diagnostics/status information	
Diagnostic messages	
• Wire-break	Yes; A break in the wire is only detected for thermocouples
• Group error	Yes
• Overflow/underflow	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes

Parameter	
Remark	4 byte
Diagnostics wire break	Disable / enable (wire break is detected only in thermocouples)
Measurement type/range	Deactivated/ ±80 mV/ ±250 mV/ ±500 mV/ ±1 V / TC-EL Type T (Cu-CuNi)/ TC-EL Type K (NiCr-Ni)/ TC-EL Type B (PtRh-PtRh)/ TC-EL Type N (NiCrSi-NiSi)/ TC-EL Type E (NiCr-CuNi)/ TC-EL Type R (PtRh-Pt)/ TC-EL Type S (PtRh-Pt)/ TC-EL Typ J
Group diagnostics	Disable / enable
Overflow/underflow	Disable / enable
Comparison point	none / RTD
Comparison point number	None / 1 / 2 / 3 / 4 / 5 / 6 / 7 / 8

Potential separation	
Potential separation analog inputs	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes

Isolation	
Isolation tested with	500 V DC

Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm

Weights	
Weight, approx.	40 g

© Copyright Siemens

last modified: 04/24/2020

Subject to change without notice
© Copyright Siemens